



75 Litre (20 Gallon) Static Overpack Maintenance Spill Kit

SK-U20

Spill kit | 75 Litre | Maintenance | Static Overpack

Absorbency: 75 Litres | 20 US Gallons**

Base Fibre: Cellulose




Product Code	Colour	Format	Size cm(inches)	Recycled Content	Units/Case	Weight/Case	LTL/Pallet	FTL/Pallet
SK-U20	Grey	Spill Kit	N/A	60%*	1	N/A	16	16

75 Litre (20 US Gallon) Static Overpack

The drum container for this spill kit keeps the absorbents clean, dry and ready for use when needed. A large gauge threaded lid and rigid construction allows the drum to be used as an overpack.

Spill kit's contents include:



50 x Pads
size 40 cm x 46 cm (16" x 18")

The pads in this spill kit are medium weight Coldform™ and feature recycled and renewable sourced natural fibres. A spun-bond lamination is added for extra strength. These pads will recover both oil and water-based fluids.



6 x Socks
size 8 cm x 1.2 m (3" x 4')

These socks feature a spun-bond outer sleeve with a durable stitched seam. This tube is then filled with a next generation super absorbent flake core and sealed with a durable metal clip.



2 x Pillows
size 23 cm x 38 cm

These pillows feature a spun-bond outer casing and a super absorbent flake core. The core is a next generation absorbent that will absorb and retain both oil-based and water-based fluids.



2 x Waste Bag

These are made from a tough grade of polythene. A cable tie is also supplied so that the waste can be secured safely.

1 pair of gloves

Waterproof gloves help to ensure safe handling of spilled substance.

1 pair of goggles

All-in one clear goggles provide eye protection from splashes.

Compliance

Related Regulations	Description
29 CFR 1910.120(j)(1)(vii)	...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.120(j)(1)(vii)	U.S. Department of Transportation specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.22(a)(2)	The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition.
40 CFR 263.31	Transporters "must clean up any hazardous waste discharge that occurs during transportation.

* Basis weights and recycled content are ± 5%

** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

*** Weight per case ± 0.5 kg/lbs.