



# 113 Litre (30 Gallon) Dash Bin Oil only Spill Kit

DASH-O30

Spill kit | 113 Litre | Oil only | Dash bin

**Absorbency:** 113 Litres | 30 US Gallons of oil\*

**Base Fibre:** Cellulose and polypropylene



Product Code	Colour	Format	Size cm(inches)	Recycled Content	Units/Case	Weight/Case	LTL/Pallet	FTL/Pallet
SK-O30	White	Spill Kit	N/A	60%*	1	N/A	8	12

## 113 Litre (30 US Gallon) Dash Bin


This spill kit is contained in a highly portable wheeled bin with a hinged lid that is ideal for locations where a quantity of sorbents need to be taken to the site of a spill at a moments notice. The wheels are made from tough rubber and cannot puncture.

### Spill kit's contents include:



**40 x Pads**  
size 40 cm x 46 cm (16" x 18")

These Oil only pads are very absorbent 240 gsm weight Coldform™ made from recycled and renewable sourced natural fibres. They have a spun-bond lamination added for extra strength.



**3 x Socks**  
size 8 cm x 1.2 m (3" x 4')

Oil only socks are made with a strong spun-bond outer sleeve and a recycled meltblown polypropylene and cellulose core, producing a resilient no-lint product.



**4 x Pillows**  
size 23 cm x 38 cm

These Oil only pillows are made from a spun-bond outer casing that is both stitched and heat sealed to enclose a recycled polypropylene core. The surface is fast-wicking so promotes faster absorption.



**4 x Waste Bag**

These are made from a tough grade of polythene. There is also a cable tie supplied so that the waste can be secured safely.

### 1 pair of gloves

Waterproof gloves help to ensure safe handling of spilled substance.

### 1 pair of goggles

All-in one clear goggles provide eye protection from splashes.

### 1 guide book

An informative booklet that advises on spill recovery.

This spill kits feature a combination of pads and socks that will contain and recover a 113 litre spill as well as the essential equipment needed to handle the clean up process.

### Notes

- Refill 10 pad packs are available for this kit.
- Ensure that disposal of these used sorbents complies with all regulations.

### Compliance

Related Regulations	Description
29 CFR 1910.120(j)(1)(vii)	...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.120(j)(1)(vii)	U.S. Department of Transportation specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.22(a)(2)	The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition.
40 CFR 263.31	Transporters "must clean up any hazardous waste discharge that occurs during transportation.

\* Basis weights and recycled content are ± 5%

\*\* Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

\*\*\* Weight per case ± 0.5 kg/lbs.