



Operating under license to  
Spill Solutions Canada Inc.

# OIL ONLY CAB MOUNT SPILL KIT

CAB-U

Spill kit | Universal | Cab Mount

**Absorbency:** 9.19 US Gallons | 34.8 Liters

**Base Fiber:** Polypropylene




Product Code	Color	Format	Size inches(cm)	Recycled Content	Units/Case	LTL/Pallet	FTL/Pallet
CAB-U	Black	Spill kit	28" X 13" X 11"	0%	1	24	24

## CAB MOUNT SPILL KIT

This spill kit is designed to be affixed to the outside of a transport vehicle for use in emergency situations. The kit features a combination of pads and socks that will contain and recover up to 9.19 US Gallons of Fluid along with the basic equipment needed to handle the clean up process. **Spill kit's contents include:**

### Notes

- Ensure that disposal of these used sorbents complies with all local, provincial and federal regulations



**15 x Pads**  
size 15" x 18"

The pads in this spill kit are Universal meltblown sonic bonded polypropylene and will absorb both oil- and water-based fluids at the same time.



**2 x Socks**  
size 3" x 4'

These socks feature a spun-bond outer sleeve with a durable heat sealed seam. This tube is then filled with a next generation super absorbent flake core and sealed with a durable metal clip.



**1 x Drain Cover**  
size 36" x 36"

This Neoprene Drain Cover is 1/16th thick and ideal for covering close by man holes or drains that may be in danger of the spill present.



**2 x Waste Bag**

These are made from a tough grade of polythene. There is also a cable tie supplied so that the waste can be secured safely.

### 1 Bag Granular

A 3 lb bag of Granular to assist in the final clean up stage

### 1 pair of gloves

Waterproof gloves help to ensure safe handling of spilled substance.

### 1 pair of goggles

All-in one clear goggles provide eye protection from splashes.

### 1 Epoxy Stick

A 4 oz Epoxy Putty designed to quickly and effectively plug leaks in fuel tanks and side walls

- \* Basis weights and recycled content are ± 5%
- \*\* Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

### Compliance

Related Regulations	Description
29 CFR 1910.120(j)(1)(vii)	...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.120(j)(1)(viii)	U.S. Department of Transportation specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.22(a)(2)	The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition.
40 CFR 263.31	Transporters "must clean up any hazardous waste discharge that occurs during transportation.